



bandsaw. This product comes without a battery or charger, both of which are available separately.





TE-MB 18/127 U Li-Solo

Item No.: 4504215

Ident No.: 21011


Bar Code: 4006825662078

The Einhell TE-MB 18/127 U Li-Solo cordless bandsaw is a high-performance member of the Power X-Change series and offers flexible operating options thanks to its removable table. Spark-free cutting of metal promises maximum safety. The angle for miter cuts is adjustable from 0° to 47° degrees, while the cutting height/width equals 115 x 127 mm. Both the saw band and the handle can be adjusted without tools. This bandsaw features a optimized speed setting and an integrated LED light. Delivery includes a second saw band and a base frame that can be combined with the

OWER X-CHANGE

Features & Benefits

- A member of the Power X-Change family
- Spark-free cutting of metal for maximum safety
- Angle for mitre cuts can be adjusted from 0 to 47°
- High cutting height/width of 115 mm x 127 mm
- Perfect speed setting for almost every application
- LED light for ideal illumination of the cutting area
- Quick-release lever for changing the band without any tools
- Handle is adjustable without tools for ergonomic working
- For flexible use with or without the base frame
- Includes a second saw band and a base frame
- Supplied without a battery or charger (available separately)





Technical Data

- Voltage 18 V - Speed 120 m/min

115 mm / 127 mm - cutting height/width - Saw band 1141 x 13 x 0.65 mm







Logistic Data

- Product weight (kg) 12.66 - Gross weight (kg) 14.3

- Dimensions single packaging 585 x 343 x 440 mm

- Pieces per export carton 1 Pieces - Gross weight of export carton 14.3 kg

- Dimensions export carton 580 x 340 x 440 mm - Container quantity (20"/40"/40"HC) 352 | 745 | 875













Available as special accessories



Sägebandset 1141x13mm 10/14Z Band Saw Accessory Item No.: 4506160 Bar Code: 4006825663112 Einhell Accessory

Battery-Running-Times

One Battery for All	cutting ¹
	(pieces)
1.5 Ah	23
2.0 Ah	30
2.5 Ah	35
3.0 Ah	45
4.0 Ah	60
5.2 Ah	78
6.0 Ah	90
8.0 Ah	120

Test setup:

¹⁾ metal - square steel tube 40x40x2mm - Max. electronic speed