





Bench Drill

TC-BD 630/1

Item No.: 4520597

Ident No.: 21012

Bar Code: 4006825668476

The Einhell bench drill TC-BD 630/1 is a precision tool for ambitious DIY enthusiasts. Due to the extra-large throat of 126 mm, large workpieces made of wood or metal can be reliably provided with pinpoint holes. With 630W power and 12-step speed adjustment from 250 to 2,400 rpm, materialappropriate and precise drilling is possible. The bench drill can thus be used at a very low as well as at a very high speed and is excellently suited both for hard materials such as metal, but also for soft material such as wood. Precise drill holes up to a maximum drilling depth of 60 mm are possible thanks to the adjustable depth stop. The bench drill is equipped with a robust sprocket chuck and an MK2 socket, which allows the use of Morse taper drills

Features & Benefits

- Powerful, guiet and maintenance-free induction motor
- 12-position variable speed for material-specific work
- Robust gear rim chuck 1.5-16 mm for common drill bit sizes
- Flexibility thanks to MK2 holder for Morse taper drill bits
- Adjustable depth stop for precise drilling, even in series
- Height-adjustable, tiltable and rotatable drill table
- Extra-large throat for machining large workpieces
- Ball bearing mounted drill spindle for long-life operation
- Three-arm turnstile for fine power control
- Sturdy steel base for a secure stand of the machine
- Folding chip guard for high safety and good visibility
- On/off switch with zero-voltage release for added safety

Technical Data

- Mains supply 220-240 V | 50 Hz - Power 630 W - Max. power (S2 | S2time) 630 W | 15 min 250 - 2400 min^-1 - Spindle speed - Number of speed steps 12 settings -45 ° - +45 ° - Drill table tiltable - Drill chuck mount B16 - Drill diameter 1.5 - 16 mm - Throat 126 mm - Max. drilling depth 60 mm

Logistic Data

- Product weight 19.4 kg - Gross weight single packaging 21.41 kg - Dimensions single packaging 700 x 425 x 260 mm - Pieces per export carton 1 Pieces - Gross weight export carton 21.41 kg - Dimensions export carton 690 x 410 x 262 mm - Container quantity (20"/40"/40"HC) 344 | 712 | 801



















