



Einhell

CLASSIC

Submersible Pump

GC-SP 3580 LL

Item No.: 4170445

Ident No.: 11016

Bar Code: 4006825615197

The Einhell clear water pump GC-SP 3580 LL is a powerful aid for homeowners and hobby gardeners. With a maximum flow rate of 8000 litres per hour, it convinces with its performance. The submersible pump already has a water level of 8 mm for starting the pump, and it can also "wipe dry" up to one millimetre of residual water on a straight surface. The high-quality mechanical seal ensures a long service life. In addition, the submersible pump has a continuously adjustable float switch and an integrated check valve, a practical cable winding and a carrying handle. Hose connection by means of a 90° angle 47.8 mm (1 1/2") OD and for 25/38 mm hoses and 33.3 mm (1") male thread. Delivery incl. Quick-Connector.

Features & Benefits

- Low level submersible up to 1 mm residual water level
- Starting of pump from water level of 8 mm already possible
- Infinitely variable floating switch
- With integrated non-return valve
- Carry-handle
- Cable rewind
- High-quality mechanical seal for a long service life
- Connector for 25 mm / 32mm hoses + G1 male thread (33.3 mm)
- 90° angle G 1½" male thread x G 1½" male thread (47.8 mm)
- Incl. Quick-Connector for fast exchange of hose

Technical Data

- | | |
|--------------------------|-------------------|
| - Mains supply | 230 V 50 Hz |
| - Power | 350 W |
| - Max. delivery capacity | 8000 L/h |
| - Max. delivery height | 7.5 m |
| - Max. immersion depth | 7 m |
| - Max. water temperature | 35 °C |
| - Hose connection | 47,8mm (G11/2 IG) |
| - Power cord | 10 m H05RN-F |

Logistic Data

- | | |
|--------------------------------------|--------------------|
| - Product weight | 3.13 kg |
| - Gross weight single packaging | 4.75 kg |
| - Dimensions single packaging | 222 x 180 x 308 mm |
| - Pieces per export carton | 4 Pieces |
| - Gross weight export carton | 19.6 kg |
| - Dimensions export carton | 460 x 380 x 320 mm |
| - Container quantity (20"/40"/40"HC) | 2000 4080 4960 |

