







### **TE-MB 18/127 U Li-Solo**

Item No.: 4504215

Ident No.: 21023


Bar Code: 4006825662078

The Einhell cordless band saw TE-MB 18/127 U Li-Solo is a powerful member of the Power X-Change family and offers flexible applications thanks to the removable table. Maximum safety is ensured by the spark-free separation of metal in use. The angle for mitre cuts is adjustable from 0°-47°, the cutting height/width is 115 x 127 mm. The handle can be adjusted without tools. The band saw has an optimal speed and an integrated LED light. Delivery includes a second saw band and a base frame that can be combined with the band saw. Delivery does not include a battery or charger. These are available separately as a starter kit

OWER X-CHANGE

## **Features & Benefits**

- A member of the Power X-Change family
- Spark-free cutting of metal for maximum safety
- Angle for mitre cuts can be adjusted from 0 to 47°
- High cutting height/width of 115 mm x 127 mm
- Perfect speed setting for almost every application
- LED light for ideal illumination of the cutting area
- Quick-release lever for easy changing of the saw band
- Handle is adjustable without tools for ergonomic working
- For flexible use with or without the base frame
- Includes a second saw band and a base frame
- Supplied without a battery or charger (available separately)





## **Technical Data**

- Voltage 18 V - Speed 120 m/min 115 mm / 127 mm - cutting height/width

- Saw band 1141 x 13 x 0.65 mm







## **Logistic Data**

- Product weight (kg) 12.66 - Gross weight (kg) 14.3

- Dimensions single packaging 585 x 343 x 440 mm

- Pieces per export carton 1 Pieces - Gross weight of export carton 14.3 kg

- Dimensions export carton 580 x 340 x 440 mm - Container quantity (20"/40"/40"HC) 311 | 656 | 772













# Available as special accessories



Sägebandset 1141x13mm 10/14Z Band Saw Accessory Item No.: 4506160 Bar Code: 4006825663112 Einhell Accessory

# **Battery-Running-Times**

One Battery for All	cutting <sup>1</sup>
	(pieces)
1.5 Ah	23
2.0 Ah	30
2.5 Ah	35
3.0 Ah	45
4.0 Ah	60
5.2 Ah	78
6.0 Ah	90
8.0 Ah	120

#### Test setup:

<sup>1)</sup> metal - square steel tube 40x40x2mm - Max. electronic speed